

06/08/99
 0670 U.S. PTO

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (12/97)

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 CFR 1.53(b))	Attorney Docket No.	16296.705	Total Pages	46
	First Named Inventor or Application Identifier			
	Paul Berkowitz			
	Express Mail Label No.	EL322090955US		

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	Assistant Commissioner for Patents ADDRESS TO: Box Patent Application Washington, DC 20231
---	---

1. ☐ Fee Transmittal Form
 (Submit an original, and a duplicate for fee processing)

2. ☒ Specification [Total Pages 35]
 (preferred arrangement set forth below)

- Descriptive title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R&D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

3. ☒ Drawing(s) (37 CFR 1.152) [Total Sheets 7]

4. ☒ Oath or Declaration [Total Pages 3]

a. ☒ Unexecuted (original or copy)

b. ☐ Copy from a prior application (37 CFR 1.63(d))
 (for continuation/divisional with Box 17 completed)
 [Note Box 5 below]

i. ☐ DELETION OF INVENTOR(S)
 Signed statement attached deleting
 inventor(s) named in the prior application,
 see 37 CFR 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (useable if Box 4b is checked)
 The entire disclosure of the prior application, from which
 a copy of the oath or declaration is supplied under Box 4b,
 is considered as being part of the disclosure of the
 accompanying application and is hereby incorporated by
 reference therein.

6. ☐ Microfiche Computer Program (Appendix)

7. Nucleotide and/or Amino Acid Sequence Submission
 (if applicable, all necessary)

a. ☐ Computer Readable Copy

b. ☐ Paper Copy (identical to computer copy)

c. ☐ Statement verifying identify of above copies

8. ☐ Assignment Papers (cover sheet & documents(s))

9. ☐ 37 CFR 3.73(b) Statement [] Power of Attorney
 (when there is an assignee)

10. ☐ English Translation Document (if applicable)

11. ☐ Information Disclosure Statement (IDS)PTO-1449 [] Copies of IDS Citations

12. ☐ Preliminary Amendment

13. ☒ Return Receipt Postcard (MPEP 503)
 (Should be specifically itemized)

14. ☐ Small Entity Statement(s) [] Statement filed in prior application, Status still proper and desired

15. ☐ Certified Copy of Priority Document(s)
 (if foreign priority is claimed)

16. ☐ Other:

17. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. ____/____

16. CORRESPONDING ADDRESS					
<input type="checkbox"/> Customer Number of Bar Code Label		021971		or <input checked="" type="checkbox"/> Correspondence address below	
(Insert Customer No. or Attach bar code label here)					
NAME	George A. Willman				
ADDRESS	WILSON SONSINI GOODRICH & ROSATI				
	650 Page Mill Road				
CITY	Palo Alto	STATE	California	ZIP CODE	94304-1050
COUNTRY	USA	TELEPHONE	(650) 493-9300	FAX	(650) 845-5000


SUBMITTED BY

Typed or

Printed Name

George A. Willman

Signature



Reg. Number 41,378

Date June 8, 1999

UNITED STATES PATENT APPLICATION

FOR

METHOD AND APPARATUS FOR ROAMING IN HIERARCHIAL MOBILE
COMMUNICATIONS NETWORK

INVENTORS:

PAUL BERKOWITZ
CHAUNCEY SHEY
JAN VANCRAEYNEST
JOSE VASCONCELLOS

PREPARED BY WILSON SONSINI GOODRICH & ROSATI

668090" 50E33E60

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to the field of communication networks. In particular, the invention relates to a method and apparatus for roaming in a mobile communications network.

Description of the Related Art

A mobile communications system may include various systems between which a subscriber may wish to travel. Often a subscriber is associated with a particular system and when the subscriber is present in a region serviced by another system, the subscriber is considered to be roaming. A subscriber's home system is typically a system for which the subscriber is registered. Several techniques allow mobile subscribers to roam into systems different from the subscriber's home system. An example is the IS-41 based system.

Some prior art systems use home location and visited location registers (HLR/VLR) and even dedicated switching networks for mobile subscribers. A disadvantage of some prior systems is the possibility of single point of failure, the need for a dedicated signaling network, the need for central coordination between entities entering into roaming agreements and difficulties in billing.

Some methods in the prior art rely on explicit rules for determining the home location of a roaming subscriber and how to handle a call to and from such a subscriber. Typically in such applications these functions are carried out by interrogation of an HLR. Such an approach introduces complexity and delay. Prior art methods also may require additional signaling traffic to establish correct billing for each call since the path may go through a different exchange than the subscriber's home exchange. Such additional signaling may be complex.

SUMMARY OF THE INVENTION

One aspect of the invention is directed to a method of modifying an existing telephone network. Interface devices serve various geographic regions of the telephone network. The interface devices are coupled to the telephone network. The interface
5 devices are coupled to circuitry coupled to radio transceivers that service mobile subscribers that may be located in ones of the geographic regions. The mobile subscribers are each assigned to a respective geographic region. When a subscriber is located in a region other than the geographic region to which the subscriber is assigned, circuitry coupled to the interface devices routes a call with a mobile subscriber through a path
10 including a radio transceiver that serves the region in which the mobile subscriber is currently located and an interface device that serves the region to which the subscriber is assigned.

One embodiment of the present invention is directed to a communications system that includes a first network dispersed throughout a national area. The communications
15 system also includes a second network coupled to the first network by interfaces in a plurality of geographic regions in the national area. The second network includes radio transceivers for communicating with subscribers located in the plurality of geographic regions. Each subscriber has a home region, and various subscribers are located outside of their home regions. The system includes circuitry that routes all communication between
20 a subscriber and the first network through an interface between the first network and the second network in the subscriber's home region.

Another embodiment of the present invention is directed to a communications system that includes a set of interfaces adapted to be coupled to a public switched telephone network (PSTN). The interfaces are configured to serve various geographic
25 regions. For communication between the PSTN and a subscriber located in a region other

than a region in which an interface to which the subscriber is assigned is located, circuitry included by the system and coupled to the set of interfaces causes the communication to take place via the interface to which the subscriber is assigned. According to one embodiment to the invention, the circuitry coupled to the set of interfaces is coupled to the interfaces via an E1 interface.

Yet another embodiment to the invention is directed to a communications system comprising radio transceivers and a set of interface devices adapted to be coupled to a PSTN. The interface devices are configured to serve various geographic regions. The radio transceivers are coupled to the interface devices in the set of interface devices. The radio transceivers are for communication with mobile subscribers. The mobile subscribers each have a home region. The circuitry coupled to the set of interfaces routes a call through a path including an interface device that serves the mobile subscriber's home region, for a call involving the PSTN and a mobile subscriber located outside the mobile subscriber's home region.

Another aspect of the invention is directed to a method of modifying an existing telephone network in which interface devices are located in various geographic regions of the telephone network. The interface devices are coupled to the telephone network in the various geographic regions. The interface devices are coupled to circuitry coupled to radio transceivers that service mobile subscribers that may be located in ones of the geographic regions. The mobile subscribers are each assigned to a respective geographic region. When a subscriber is located in a region other than the geographic region to which the subscriber is assigned, circuitry coupled to the interface devices routes a call with a mobile subscriber through a path including a radio transceiver in the region in which the mobile subscriber is currently located and an interface device in the region to which the subscriber is assigned.

In yet another embodiment of the invention, each subscriber is associated with one or more directory numbers. Routing of incoming calls is conditioned upon a subscriber profile when the subscriber is out of the subscriber's home geographic region. Incoming calls may be routed to the subscriber in the subscriber's new location or to another subscriber or to voice mail depending on the subscriber's feature profile and which directory number with which the call is associated. If a subscriber has for example directory numbers 1, 2, 3 assigned, the subscriber may set up the subscriber profile to cause the interface device to act as follows when the subscriber is out of the area:

- for incoming calls associated with number 1, route to the subscriber's new location ("follow-me" number);
- for incoming calls associated with number 2, route another directory number; or
- for incoming calls associated with number 3, route to voice mail.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a block diagram of a telephone communications system, according to an embodiment of the invention.

FIG. 2 is a block diagram illustrating circuitry acting as a proxy for radio ports belonging to other interface devices for terminating calls, according to an embodiment of the invention.

FIG. 3 is a block diagram illustrating circuitry acting as a proxy for network ports for a first interface for calls originating from mobile subscribers assigned to another region, according to an embodiment of the invention.

FIG. 4 is a flow diagram of location registration, according to an embodiment of the invention.

FIG. 5 is a flow diagram of an originating call process, according to an embodiment of the invention.

FIG. 6 is a flow diagram of a terminating call process, according to an embodiment of the invention.

5 FIG. 7 is a flow diagram of an interface handover process, according to an embodiment of the invention.

FIG. 8 is a block diagram illustrating the circuitry that routes calls configured as regional circuitry interconnected centrally, according to an embodiment of the invention.

10 FIG. 9 is a block diagram illustrating expanded circuitry for routing calls connected by a local or distributed control bus, according to an embodiment of the invention.

FIG. 10 is a block diagram illustrating circuitry that routes calls implemented in a mesh configuration, according to an embodiment of the invention.

15 FIG. 11 is a block diagram showing circuitry that routes calls configured to route calls to home interfaces through the public switched telephone network (PSTN) by including a gateway functionality inside interface devices, according to an embodiment of the invention.

DETAILED DESCRIPTION

One embodiment of the invention is directed to a system for routing calls when subscribers are located outside of the coverage area of an interface to the public network in their home area. When such a subscriber wants to make a call, the circuitry routes the call to an interface to the public network that serves the home area. Similarly, incoming calls from the public network are routed through the interface that services the home region, to equipment in the region outside of the home region where the subscriber is currently located. Such an arrangement has an advantage of, according to one embodiment, making roaming transparent to the public network and billing systems.

FIG. 1 is a block diagram of a telephone communications system, according to an embodiment of the invention. The system includes interface devices that are coupled to the public network (NIU_A 111, NIU_B 112, and NIU_C 113). Radio port controllers are coupled to the various interfaces -- as shown, NIU_A 111 is coupled to RPC_{A1} 115 and RPC_{A2} 117, NIU_B 112 is coupled to RPC_{B1} 119 and RPC_{B2} 121, and NIU_C 113 is coupled to RPC_{C1} 124 and RPC_{C2} 125. The radio port controllers are coupled to radio transmitters -- RPC_{A1} 115 is coupled to radio transceivers 116, RPC_{A2} 117 to radio transceivers 118, RPC_{B1} 119 is coupled to radio transceivers 120, RPC_{B2} 121 is coupled to radio transceivers 122, RPC_{C1} 124 is coupled to radio transceivers 126, and RPC_{C2} 125 is coupled to radio transceivers 127. Radio transceivers are used to communicate with mobile subscribers, for example, PS_A 123. Radio transceivers include radio ports and appropriate transceiver circuitry.

The interfaces each serve a different geographic region by being coupled, through the radio port controllers, to radio transmitters that serve the respective geographic region. According to one embodiment of the invention, such interfaces are located in the

respective regions that they serve. According to another embodiment of the invention, such interfaces are not necessarily located in the respective regions that they serve. For example, the interfaces may be co-located.

Circuitry ATC₁ 114 couples the various interface devices (NIU_A 111, NIU_B 112, and NIU_C 113. Circuitry ATC₁ 114 may be implemented in the form of dedicated circuits, or a computerized system. Typically, circuitry ATC₁ 114 includes bearer channels and control channels. E1 links are provided to interconnect the various interface devices via ATC₁ 114. Circuitry that routes calls between interface devices, circuitry ATC as shown in Fig. 1, may be implemented as a computer system. The ATC circuitry acts as a controller and includes an E1 interface. The circuitry ATC includes bearer and control circuitry. The bearer circuitry provides a path for transmission of information, such as voice from a subscriber, to the correct interface. Such transmission typically occurs over an E1 interface. The circuitry that routes between the interfaces (e.g., ATC) includes a cross connect, which is a split that maps between various incoming and outgoing lines. An ATC may have, in one example, 30 multiplexed lines.

An interface device, shown in FIG. 1 as, for example, NIU_A 111, may be implemented as a computer with controllers. The interface device includes interface boards for interfacing with radio port controllers (e.g., RPC_{A1} 115). Such interfacing takes place typically via an E1 standard. The interface from the interface device to the PSTN (PSTN 110) may take place via an analog, T1 interface, or other interface. The interface device is typically coupled to a class 5 switch in the PSTN.

According to one embodiment of the invention, an interface device can have a large number of subscribers assigned to it, e.g., 10,000 subscribers, and a large number of roaming subscribers. According to one embodiment of the invention, subscribers are registered in a particular home interface device for billing purposes and because of

telephone number assignment to the particular PSTN ports to which the home interface device is connected. The sizing of connectivity between interface devices and circuitry ATCs is determined by the amount of roaming traffic between respective interface devices and the desired grade of service for such roaming traffic.

5 When a subscriber, for example, PS_A 123 is located out of the subscriber's home area, the following may occur, according to an embodiment of the invention. Radio ports under a network interface emit a paging area identifier unique for each network interface. This paging area identifier is received by subscribers in the network interface's coverage area. As a subscriber moves away from the region served by the subscriber's home network interface device, say, NIU_A 111, it notices that the paging area identifier changes. The subscriber then knows that it has moved into the coverage area of a new network interface device. At this point, the subscriber, say PS_A 123, sends a registration message including its own identification to the new network interface device, say NIU_B 112. NIU_B 122 receives the registration request and notices from the subscriber identification that PS_A 123 is not assigned in an NIU_B's 112 database.

NIU_B 112 forwards a registration request to circuitry ATC₁ 114. ATC₁ 114 either knows about the subscriber PS_A 123 (through previous registration or calls made by a subscriber PS_A 123) or does not know about subscriber PS_A 123. If ATC₁ 114 knows about subscriber PS_A 123, then circuitry ATC₁ 114 updates the location entry in its database for subscriber PS_A 123 to indicate that the subscriber PS_A 123 is located in the area covered by interface device NIU_B 112 and sends the registration request on to interface device NIU_A 111. If circuitry ATC₁ 114 does not know about subscriber PS_A 123, then circuitry ATC₁ 114 sends the registration request on to NIUs connected to ATC₁ 114 except to the interface device that originated the request. In this case, for example, the registration request is sent to interface device NIU_A 111 and interface device NIU_C 113 but

not to interface device NIU_B 112. The one interface device recognizes the subscriber PS_A 123 from the subscriber identification contained in the registration message. Such interface device recognizes subscriber PS_A 123 as assigned to that interface device's database and responds to the registration request. The circuitry ATC₁ 114 then updates its table to reflect that subscriber PS_A 123 belongs to interface device NIU_A 111 and is currently assigned to NIU_B 112.

In another embodiment of the invention, subscriber PS_A 123 is programmed with the identity of its assigned or home region, or is programmed with the identity of the assigned or home network interface device. According to one embodiment of the invention, such assignment is made at the time the subscriber is activated for service and has the ability to inform the network about the subscriber's home region and/or corresponding interface device. Upon receipt of such notification, an interface device serving each visited region can directly forward the registration to the proper home interface device through the circuitry ATC.

In another embodiment of the invention, each interface device and circuitry ATC can deduce from the construction of the subscriber identification to which region the subscriber belongs. The registration is then forwarded to the proper home interface device corresponding to the region through the circuitry ATC. An example of such subscriber identification structuring is the use of prefixes unique to each interface device.

When a call comes in for subscriber PS_A 123 from the public network (terminating call), interface device NIU_A 111 sends a page request to radio port controllers under NIU_A 111 and also to circuitry ATC₁ 114. Because subscriber PS_A 123 is outside of the coverage of network interface NIU_A 111, none of the radio port controllers under interface device NIU_A 111 respond with a positive page acknowledgement. If circuitry ATC₁ 114 knows about subscriber PS_A 123, it forwards the page to the NIU under whose coverage it

knows subscriber PS_A 123 to have most recently been in (for example, to interface device NIU_B 112). If circuitry ATC₁ 114 does not know about subscriber PS_A 123, circuitry ATC₁ 114 sends the page to all interface devices coupled to circuitry ATC₁ 114, except to the originating interface device (in this case, to interface device NIU_B 112 and interface device NIU_C 113, but not to interface device NIU_A 111). The interface device that has subscriber PS_A 123 under its coverage responds to the page. Circuitry ATC₁ 114 forwards the page response to the home interface device and establishes a call path between a home interface device, through circuitry ATC₁ 114, through a visited interface device and to subscriber PS_A 123. Authentication and alerting are also performed. An advantage of such a configuration is that a call may be delivered to subscriber PS_A 123 without the home interface device, interface device NIU_A 111, explicitly knowing the location of subscriber PS_A 123.

In another embodiment to the invention, the home interface device keeps track of the location of each subscriber assigned to it by communication from circuitry ATC and therefore can directly page the correct radio port controller for a terminating call without having the circuitry ATC broadcast the page to all interface devices connected to it. Because the home interface device updates its database as the location is updated in the circuitry ATC, an advantage is gained that the interface device does not need to query the circuitry ATC.

Having the home interface device keep track of the location of each subscriber assigned to it also allows the home interface to make different routing decisions when the subscriber is out of the subscriber's home coverage area, according to one embodiment of the invention. When a single subscriber is associated with multiple directory numbers, such an approach may provide an advantage. Incoming calls associated with each of the directory numbers may be routed differently depending on instructions in the subscriber's

service profile. For instance, calls associated with (directed to) the subscriber's first directory number may be routed to the subscriber's new location ("follow-me" service), calls associated with a subscriber's second directory number may be sent to voice mail, and calls associated with a subscriber's third directory number may be routed to another subscriber.

When subscriber PS_A 123 wants to originate a call from the coverage area of a visited region covered by interface device NIU_B 112, subscriber PS_A 123 sends a set-up message to interface device NIU_B 112. Then NIU_B 112 recognizes that subscriber PS_A 123 is not assigned in the database of interface device NIU_B 112. Call handling proceeds as in the case of registration and the call path is established between subscriber PS_A 123 through the interface device NIU_B 112 in the visited region, through circuitry ATC₁ 114 and home interface device NIU_A 111. An advantage of such a configuration is that the call from subscriber PS_A 123 is delivered to the network without the interface device which makes contact with subscriber PS_A 123 necessarily knowing which interface device is the home interface device for subscriber PS_A 123.

According to one embodiment of the invention, the same messages are exchanged between the interface device and the circuitry ATC for traveling subscribers as are exchanged between the interface device and radio port controllers for a home subscriber.

In another embodiment of the invention, subscriber PS_A 123 is programmed with the identity of its home region or corresponding home interface device at the time the subscriber is activated for a service. The subscriber has the ability to inform the network about its home region or interface device. Upon receipt of such notification with a call set-up message, each visited region's interface device can directly forward the call to the proper home interface device through the circuitry ATC.

In another embodiment to the invention, each interface device and circuitry ATC can deduce from the construction of a subscriber identifier which region or interface device the subscriber belongs to and directly forward the registration to the proper home interface device through the circuitry ATC. An example of such subscriber ID structuring is the use of prefixes unique to each interface device or region.

When a subscriber moves from the coverage of a radio port belonging to a first interface device to the coverage of another radio port belonging to an interface device different from the first interface device, the subscriber initiates a handover by dropping the connection to the old radio port and requesting a new connection to the new radio port.

The circuitry ATC processes the set-up messages similarly to a regular originating call, with the exception that authentication steps are skipped to reduce the time to set the new handover call and with the exception that the circuitry ATC retains any parts of the existing call that are common to the handover call.

Since calls enter or leave the mobile communications network through the home interface device of a subscriber even when the subscriber is located outside of the subscriber's home region, according to one embodiment of the invention, no change is needed in the billing methods of the public switched telephone network (PSTN) to which the mobile communications network connects. If an operator optionally wishes to bill differently for roaming calls, this flexibility is provided through separate call detail records which record call information such as which radio port and interface devices are involved in each call.

FIG. 2 is a block diagram illustrating circuitry acting as a proxy for radio ports belonging to other interface devices for terminating calls, according to an embodiment of the invention. Thus, this shows that circuitry ATC may act logically like another radio port controller coupled to an interface device. For example, here interface device

NIU_A211 is coupled to radio port controller RPC_{A1} 212 and radio port controller
RPC_{A2} 214. Circuitry ATC 216 routes calls to respective interface devices (not shown)
thus logically allowing access through interface device NIU_A 211 to radio port controllers
RPC_{C1} 221, RPC_{C2} 223, RPC_{B1} 217, and RPC_{B2} 219. Thus, subscriber PS_A 230, whose
5 home interface device is interface device NIU_A 211, is provided access to PSTN 210 via
remote radio ports serving a region outside of subscriber's PS_A 230 home region. Thus,
logically, the ATC 216 circuitry makes radio ports 222, 224, 218, and 220, which serve a
remote region, appear like local radio ports coupled to home interface device NIU_A 211.

FIG. 3 is a block diagram illustrating circuitry acting as a proxy for network ports
10 for a first interface for calls originating from mobile subscribers assigned to another
region, according to an embodiment of the invention. An originating call is placed from
subscriber PS_A 320, currently located in the region of network interface NIU_B 317. This
call is received by a radio port among radio ports 319, which are coupled to radio port
controller RPC_{B1} 318. Radio port controller RPC_{B1} 318 is coupled to interface device
15 NIU_B 317, which is coupled to PSTN 310. However, the call is routed through an ATC to
interface device NIU_A 311 through which the call is then routed to the PSTN 310. Thus, a
virtual connection exists from interface device NIU_B 317 into a portion of the PSTN to
which interface device NIU_A 311 is coupled. This is shown in the figure as the connection
between interface device NIU_B 317 and PSTN 316. Similarly, connection is provided
20 virtually from interface device NIU_C 323 to PSTN 310. This connection takes place
physically through a connection between interface device NIU_C 323 and interface device
NIU_A 311. However logically, it is as if there is a connection between interface device
NIU_C 323 at the portion of the PSTN to which interface device NIU_A 311 is connected.
This is shown here as a connection between interface device NIU_C 323 and PSTN 324.

FIG. 4 is a flow diagram of the location registration process, according to an embodiment of the invention. Fig. 4 has various lines representing communication with the following entities: PSTN 410, NIU_A 411, NIU_B 412, NIU_C 413, RPC_{B1} 414, RPC_{B2} 415, ATC 416, and PS_A 417. First a registration message is received by a radio port and forwarded to the radio port controller. As shown here, location registration 418 is sent from subscriber PS_A 417 to radio port RPC_{B1} 414. In this case, subscriber PS_A 417 is located in the coverage area of radio port controller RPC_{B1} 414, which is not the home location of subscriber PS_A 417. Radio port controller RPC_{B1} 414 sends a message to its respective interface device, interface device NIU_B 412 (line 419). Interface device NIU_B 412 does not recognize subscriber PS_A 417. Thus interface NIU_B 412 sends a message to the circuitry ATC 416 (line 420). Assuming that ATC 416 has not yet stored PS_A 417 in its database, then ATC 416 queries other interface devices to determine the home location for subscriber PS_A 417 (lines 421 and 422, which are sent to interface device 411 NIU_A and interface device NIU_C 413, but not interface device NIU_B 412).

In this example, subscriber PS_A 417 belongs to interface device NIU_A 411. Thus, interface device NIU_A 411 responds (authorization request 423). ATC 416 forwards this response to interface device NIU_B 412. Interface device NIU_B 412 then sends the authorization request 428 to interface device NIU_B 412. An authorization response is sent back (429) from interface device NIU_B 412 to circuitry ATC 416. The authorization response is then sent from circuitry ATC 416 back to interface device NIU_A 411. Interface device NIU_A 411 determines whether the subscriber PS_A 417 should be authenticated, and can then make future determinations based on this authentication.

FIG. 5 is a block diagram of an originating call process, according to an embodiment of the invention. Here it is assumed that subscriber PS_A 517 is already registered at the particular location and that the circuitry ATC knows that subscriber

PS_A 517 belongs to interface device NIU_A 511. Subscriber PS_A 517 is located in the coverage area of interface device NIU_B 512. Thus, subscriber PS_A 517 sends a set-up request 518 to radio port controller RPC_{B1} 514. This request is forwarded to interface device NIU_B 512 (line 519). Interface device NIU_B 512 signals circuitry ATC's 516 (line 520). Because circuitry ATC 516 knows that subscriber PS_A 517 belongs to interface device NIU_A 511, circuitry ATC 516 signals interface device NIU_A 511. Interface device NIU_A 511 makes an authorization request (line 522) to circuitry ATC 516. In response, circuitry ATC 516 forwards the request to interface device NIU_B 512 (line 523), and interface device NIU_B 512 forwards the request to radio port controller RPC_{B1} 514, which forwards the message to subscriber PS_A 517 (line 525). An authentication response is returned from subscriber 517 to radio port controller RPC_{B1} 514 (line 525), and this result is forwarded to interface device NIU_B 512 (line 527), and to circuitry ATC 516 (line 528) and back to interface device NIU_A 511 (line 529). If the authentication result is good, then NIU_A 511 makes a set-up request to the PSTN 510 (line 530). A connect response is received from PSTN 510 to interface device NIU_A 511 (connect line 531). The PSTN makes necessary set-up in order to connect the message back.

The connect message is then forwarded to circuitry ATC 516 from interface device NIU_A 511 (line 532). This response is forwarded from circuitry ATC 516 to interface device NIU_B 512 (line 533) and subsequently to radio port controller RPC_{B1} 514 and on to subscriber PS_A 517 (lines 534 and 535). A communications connection is then set up between subscriber PS_A 517 and PSTN 510. The communications path includes subscriber PS_A 517, radio port controller RPC_{B1} 514, interface device NIU_B 512, circuitry ACT 516, interface device NIU_A 511, and PSTN 510. In this way, a call path is established between a subscriber (PS_A 517) and the public-switched telephone network (PSTN 510) by way of the subscriber's home interface device (NIU_A 511).

FIG. 6 is a flow diagram of a terminating call process, according to an embodiment of the invention. Shown here is communication between entities: public switched telephone network PSTN 610, interface device NIU_A 611, interface device NIU_B 612, interface device NIU_C 613, radio port controller RPC_{B1} 614, radio port controller RPC_{B2} 615, circuitry ATC 616, radio port controller RPC_{A1} 617, radio port controller RPC_{A2} 618, and subscriber PS_A 619. When a call originates from PSTN 610, its set-up request is sent from PSTN 610 to interface device NIU_A 611 (set-up 620). This set-up request is made to interface device NIU_A 611 because that interface device is the home interface device for subscriber PS_A 619. Interface device NIU_A 611 sends a set-up request to the radio port controllers coupled to interface device NIU_A 611 (radio port controller RPC_A, radio port controller RPC_{A1} 617, and radio port controller RPC_{A2} 618, via set-up request 622 and 623). A set-up request is also sent to ATC 616 (set-up 621). This set-up 621 is sent to ATC 616 because ATC 616 looks to interface device NIU_A 611 like another radio port controller.

Circuitry ATC 616 sends a set-up request to interface device NIU_B 612 (line 624). Interface device NIU_B 612 sends the set-up request to radio port controllers located in the areas of interface device NIU_B 612 (radio port controller RPC_{B1} 614 and radio port controller RPC_{B2} 615, lines 625 and 626). A page is then made by radio port controller RPC_{B1} 614 (page 627 from radio port controller RPC_{B1} 614 to subscriber PS_A 619).

Subscriber PS_A 619 responds to radio port controller RPC_{B1} 614 (page response 628).

The response is forwarded to the local interface device (line 629 to interface device NIU_B 612) and on the circuitry ATC 616 (line 630). Response is forwarded to the home interface device (line 631 from ATC 616 to interface device NIU_A 611). Interface device NIU_A 611 responds with an authorization authentication request 650 to circuitry ATC 616.

Circuitry ATC 616 forwards the authentication request to interface device NIU_B 612

(line 632), which forwards the request (line 633) to radio port controller RPC_{B1} 614.

Radio port controller RPC_{B1} 614 forwards the request to subscriber PS_A 616

(authentication request 634). Subscriber PS_A 619 provides an authentication response 635

to radio port controller RPC_{B1} 614, which forwards the result (636 to interface device

5 NIU_B 612). The result is additionally forwarded to circuitry ATC 616, and along to

interface device NIU_A 611. The interface device NIU_A 611 responds with an alert 640 to

circuitry ATC 616. The alert is forwarded to the interface located near the subscriber,

interface NIU_B 612 (line 641) and is additionally forwarded to radio port controller

RPC_{B1} 614 (line 642), and further to subscriber PS_A 619 (alert 643). The alert causes the

10 subscribers device to ring, for example. The subscriber answers (line 644). This answer is

forwarded from radio port controller RPC_{B1} 614 and on to the local interface device NIU_B

612 (line 645), and on to circuitry ATC 616 (box 646), and on to the home interface

device NIU_A 611 (line 647). A connect message is returned to the public switched

network PSTN 610 (connect 648).

15 The call is then established between the PSTN 610 and subscriber PS_A 619 via the

subscriber's home interface device NIU_A 611. The path includes PSTN 610, interface

device NIU_A 611, circuitry ATC 616, interface device NIU_B 612, radio port controller

RPC_{B1} 614 and subscriber PS_A 619 (communication in progress line 649).

FIG. 7 is a flow diagram of an interface handover process, according to an

20 embodiment of the invention. First a connection is established between subscriber

PS_A 719 and PSTN 710 via subscriber's home interface device NIU_A 711 and the interface

device that serves the region in which the subscriber is currently located, NIU_B 712. Later

the subscriber PS_A 719 moves from the coverage area of interface device NIU_B 712 and

into the coverage area of interface device NIU_C 713. A disconnect signal is sent from

25 subscriber PS_A 719 to radio port controller RPC_{B1} 714, which is covered by interface

device NIU_B 712 (disconnect line 721). A set-up signal is sent from subscriber PS_A 719 to radio port controller NIU_{C1} 717, which serves the region in which the subscriber is now located (set-up line (hand-over) 722). Radio port controller NIU_{C1} 717 forwards this set-up request to the local interface device NIU_C 713 (line 723). This request is then

5 forwarded to circuitry ATC 716 (line 724). A connect request is sent to the now local interface device NIU_C 713 (line 725) from circuitry ATC 716. Now a release can be sent from circuitry ATC 716 to the old local interface device NIU_B 712. A connect request is then sent from the new interface device NIU_C 713 (connect 727) to the local radio port controller RPC_{C1} 717 (connect 727). Authentication, according to one embodiment of the invention is not performed at this point.

FIG. 8 is a block diagram illustrating the circuitry that routes calls configured as regional circuitry interconnected centrally, according to an embodiment of the invention. Regional ATC R-ATC₁ 811 is coupled to interface devices that are located geographically closer to circuitry R-ATC₁ 811 (NIU_D 714, NIU_E 715, and NIU_F 716). Another regional circuitry R-ATC₂ 812 located in another geographic area is coupled to interface devices geographically close to it (NIU_A 817, NIU_B 818, and NIU_C 819). The circuitry is coupled via a connecting device 813, which couples R-ATC_C 811 and R-ATC₁ 812. The various interface devices are coupled to the PSTN 810. The regional circuits (R-ATC₁ 811 and R-ATC₂ 812 are located geographically close to the interface devices that they service.

15

20 Alternatively, the circuits are coupled to interface devices that are likely to have traffic between them.

FIG. 9 is a block diagram illustrating expanded circuitry for routing calls connected by a local or distributed control bus, according to an embodiment of the invention. The particular circuitry that is used to interconnect interface devices may have

25 physical limits in terms of numbers of interconnections it can support, or other limitations.

Therefore multiple such circuits may be combined as shown. Here, ATC block 911 is used to couple interface device NIU_A 912 and interface device NIU_D 913 and other interface devices between them, which are couple to the PSTN 910. The circuitry ATC block 911 is comprised of S-ATC 914, which is responsible for signaling and expansion circuits E-ATC₁ 915 and E-ATC₂ 916. The bearer capability of the ATC block 911 is expanded by connecting multiple expansion ATCs (E-ATC) between interface devices. The expansion ATCs are under control of the signaling ATC (S-ATC) over a common bus 917. Individual interface devices connect to one or more expansion ATCs and the signaling ATC. The signaling ATC coordinates time slot arrangements between each interface device and one or more of the expansion ATCs.

FIG. 10 is a block diagram illustrating circuitry that routes calls implemented in a mesh configuration, according to an embodiment of the invention. Mesh of circuits 1011, which routes calls between interfaces, comprises M-ATC 1012, M-ATC 1013, and M-ATC 1014. Such circuits 1012, 1013, and 1014 are interconnected in a mesh fashion whereby one circuit is coupled to more than one other circuit. Here, for example, circuit M-ATC 1012 is coupled to both circuit M-ATC 1013 and circuit M-ATC 1014. Circuit M-ATC 1014 is also coupled to circuit M-ATC 1013. An advantage of such a configuration is that a failure of a single circuit ATC may merely reduce the grade of service but does not necessarily destroy connectivity among the interface devices. Circuits 1011 may be advantageously partitioned based on roaming statistics between interface devices with adjacent coverage areas. For example, subscribers may typically roam between interface device NIU 1020, interface device NIU 1019, interface device NIU 1021, and interface device NIU 1022. For this reason, the regional circuits R-ATC 1018 and R-ATC 1017 may be coupled to the same circuit in the mesh, circuit M-ATC 1012. The association between interface devices and regional circuits may be determined based

on typical roaming patterns. For example, subscribers may typically roam between interface devices NIU 1020 and NIU 1019. For this reason, for example, such interface devices may be coupled to a single regional circuit R-ATC 1018.

Under one embodiment of the invention, calls with a subscriber located outside of the subscriber's home region may be routed via the PSTN to the interface device that serves in the subscriber's home region. Then, the call is routed from the interface device that serves the subscriber's home region back into the PSTN. The routing from the equipment serving visited region to the home region's interface device takes place via connections in the PSTN 1110 without specifically billing the subscriber for such connections. Here interface devices NIU_A 1111, NIU_B 1112, and NIU_C 1113 are coupled by a control bus 1114, which is coupled to a circuit 1115. Calls with subscribers located in their home regions are routed between respective interface devices serving the home region and the PSTN 1110. Calls with a subscriber located outside of the subscriber's home region are routed through an interface device serving the region outside of the home region into the PSTN 1110 to the interface device serving the subscriber's home region, and then back into the PSTN 1110.

The routing of calls with roaming subscribers through the PSTN to the home interface takes place through a different type of routing than routing of a typical call directly to a subscriber. In one example, the routing takes place by way of a set of routing numbers reserved for routing roaming calls or other calls other than typical calls directly with subscribers. The routing numbers may be assigned in advance or may be dynamically allocated and released out of a pool of roaming numbers. Such allocation out of a pool of numbers may be made based on desired grade of service for the roaming calls. For a related discussion, see U.S. Pat. No. 5,353,340 by Kunz, which is incorporated herein by reference.

Circuitry 1115 (which may be referred to as a network ATC) may coordinate the assignment, release, and dissemination of such PSTN routing numbers among the interface devices. Circuitry 1115 may determine the home region or home interface device of a subscriber located outside of the subscriber's home region. Signaling information for such processes may be transferred over a control bus 1114, into the interface devices and circuitry 1115.

For an example of operation of such an approach, consider a case in which a subscriber is located outside of the subscriber's home region. For example, a subscriber has a home region associated with interface device NIU_A 1111, and the subscriber is currently located in an area covered by interface device NIU_C 1113. Interface device NIU_C 1113 recognizes that the subscriber is a roaming subscriber. By way of an interface, shown here as roaming gateway 1118, the bearer channel for the subscriber includes a path with connection 1124 from visited interface NIU_C 1113 into the PSTN 1110 via connection 1125 and to the home interface device NIU_A 1111 via connection 1120. The path also includes the connection 1119 from the home interface 1111 into PSTN 1110. The path through the PSTN 1125 takes place via a special assigned number, rather than a number associated with the particular subscriber. In this way, a roaming subscriber's call is routed from the visited interface device through the PSTN to the home interface device and back into the PSTN.

Roaming gateway 1116 of interface device NIU_A 1111 is coupled to the PSTN by connection 1120, which represents a special connection for the purpose of routing roaming calls through the PSTN to the home interface device. Similarly, roaming gateway 1117 of interface device NIU_B 1112 is coupled via line 1122 to PSTN 1110, and roaming gateway 1118, which is located in interface device NIU_B 1113 is coupled to PSTN 1110 via connection 1124. Connections 1125, 1126, and 1127 connect the respective roaming

gateways for routing roaming calls back to their respective home interfaces through which they are routed back into the PSTN 1110.

Another embodiment of the invention is directed to a communications system and set of interfaces adapted to be coupled to a cable network. The cable network may
5 comprise, in one example, a cable television network. The cable television network may comprise a coax network, a fiber network, or a hybrid fiber and coax network. Circuitry coupled to the interfaces routes transmissions of information to selected interfaces from among the set of interfaces adapted to be coupled to the network.

The foregoing description of various embodiments of the invention has been
10 presented for purposes of illustration and description. It is not intended to limit the invention to the precise forms disclosed. Many modifications and equivalent arrangements will be apparent.

CLAIMS

What is claimed is:

1 1. A method of modifying an existing telephone network, the method
2 comprising:
3 coupling interface devices to the telephone network, the interface devices coupled
4 to circuitry coupled to radio transceivers that service mobile subscribers that may be
5 located in ones of the various geographic regions, the mobile subscribers each being
6 assigned to a respective geographic region;

7 wherein the interface devices are coupled to circuitry that, when a subscriber is
8 located in a region other than a geographic region to which the subscriber is assigned,
9 routes a call with the mobile subscriber through a path including a radio transceiver that
10 serves the region in which the mobile subscriber is currently located and an interface
11 device that serves the region to which the subscriber is assigned.

12 2. The method of claim 1, wherein the existing telephone network comprises a
2 public switched telephone network (PSTN).

3 3. The method of claim 1, wherein the path between the radio transceiver and
4 the interface device in the region to which the subscriber is assigned does not include the
5 existing telephone network.

1 4. The method of claim 1, wherein the path between the radio transceiver and
2 the interface device that serves the region to which the subscriber is assigned includes the
3 existing telephone network.

1 5. The method of claim 1, wherein the path between the radio transceiver and
2 the interface device that serves the region to which the subscriber is assigned includes an
3 E1 link.

1 6. The method of claim 1, wherein the path between the transceiver and the
2 interface device that serves the region to which the subscriber is assigned includes an
3 interface that serves the region in which the subscriber is located.

1 7. The method of claim 1, wherein the path between the transceiver and the
2 interface device that serves the region to which the subscriber is assigned includes a
3 device that is coupled to the interface devices via bearer and control channels.

1 8. The method of claim 1, wherein, for calls with the subscriber located in a
2 region other than the geographic region to which the subscriber is assigned, billing
3 information is passed to the existing network regarding location of the subscriber only
4 through the interface that serves the region to which the subscriber is assigned.

1 9. A communications system comprising:
2 a first network dispersed throughout a national area;
3 a second network coupled to the first network by interfaces in a plurality of
4 geographic regions in the national area, the second network including radio transceivers

5 for communicating with subscribers located in the plurality of geographic regions, each
6 subscriber having a home region, various subscribers being located outside of their home
7 regions; and

8 circuitry that routes all communication between a subscriber and the first network
9 through an interface between the first network and the second network in the subscriber's
10 home region.

1 10. The communications system of claim 9, wherein the first network
2 comprises a PSTN.

3 11. The communications system of claim 9, wherein the circuitry that routes all
4 communication includes a computer coupled to bearer and control channels coupled to the
5 interfaces for routing, between the respective interfaces, calls with subscribers located
6 outside their respective home regions.

7 12. A communications system comprising:
8 a set of interfaces adapted to be coupled to a PSTN, the interfaces configured to
9 serve various geographic regions;
10 circuitry coupled to the set of interfaces that, for communication between the
11 PSTN and a subscriber located in a region other than a region served by an interface to
12 which the subscriber is assigned, causes the communication to take place via the interface
13 to which the subscriber is assigned.

1 13. The communications system of claim 12, wherein the circuitry coupled to
2 the set of interfaces is coupled to the interfaces via an E1 interface.

1 14. The communications system of claim 12, wherein communication between
2 the circuitry coupled to the set of interfaces and the subscriber takes place entirely over a
3 land line system.

1 15. The communications system of claim 12, including circuitry coupled to the
2 set of interfaces that converts a signal from the subscriber to packets before passing the
3 signal to the PSTN.

1 16. The communications system of claim 12, wherein communication between
2 the circuitry coupled to the set of interfaces and the subscriber takes place at least partially
3 by radio transmission.

1 17. A communications system comprising:
2 a set of interface devices adapted to be coupled to a PSTN, the interface devices
3 configured to serve various geographic regions;
4 radio transceivers coupled to interface devices in the set of interface devices, the
5 radio transceivers for communication with mobile subscribers, the mobile subscribers each
6 having a home region; and
7 circuitry coupled to the set of interface devices that, for a call involving the PSTN
8 and a mobile subscriber located outside the mobile subscriber's home region, routes the
9 call through a path including an interface device that serves the mobile subscriber's home
10 region.

1 18. The communications system of claim 17, wherein, for a call to a mobile
2 subscriber, the circuitry coupled to the set of interfaces determines the region in which the
3 mobile subscriber is located and routes the call through a path including the interface that
4 serves the mobile subscriber's home region and the interface that serves the region in
5 which the mobile subscriber is located.

1 19. The communications system of claim 17, wherein the subscriber has a set
2 of directory numbers and each call is associated with at least one directory number, and
3 for a call to the mobile subscriber, the circuitry coupled to the set of interfaces, upon
4 detecting that the mobile subscriber is located outside the mobile subscriber's home
5 region, routes the call depending on instructions in a subscriber service profile, the
6 instructions being associated with the directory number that is associated with the call.

1 20. The communications systems of claim 19, wherein, depending on the
2 instructions in the subscriber service profile, the call is routed to one of (a) the subscriber,
3 (b) another subscriber, and (c) a voice mail box.

1 21. The communications system of claim 17, wherein, for a call from a mobile
2 subscriber, the circuitry coupled to the set of interfaces routes the call through a path
3 including the interface in the region in which the mobile subscriber is located and the
4 interface in the mobile subscriber's home region.

1 22. The communications system of claim 17, wherein the mobile subscriber has
2 a transceiver with circuitry that transmits information regarding the mobile subscriber's
3 home region to the circuitry coupled to the set of interfaces.

1 23. The communications system of claim 17, wherein the circuitry coupled to
2 the set of interfaces comprises computer systems located in different areas, a computer
3 system located in each respective area routing calls between the interfaces in the
4 respective area.

1 24. The communications system of claim 17, wherein the circuitry coupled to
2 the set of interfaces comprises multiple computer systems, each computer system coupled
3 to sets of bearer and control channels and each computer system coupled to the other
4 computer systems by a common control bus.

1 25. The communications system of claim 24, wherein the common control bus
2 comprises a physically localized local area network.

1 26. The communications system of claim 24, wherein the common control bus
2 comprises a physically distributed internet.

1 27. The communications system of claim 23, wherein the computer systems
2 located in each respective area are coupled to multiple others of the computer systems
3 located in the respective other areas.

1 28. The communications system of claim 17, wherein the circuitry that routes
2 the call routes the call through a path including the PSTN between the mobile subscriber
3 and the interface device that serves the subscriber's home region.

1 29. The communications system of claim 17, wherein the interface devices
2 include roaming gateways coupled to the PSTN and coupled via a control bus to the
3 circuitry that routes the call.

1 30. The communications system of claim 29, wherein the control bus
2 comprises a physically localized local area network.

1 31. The communications system of claim 29, wherein the control bus
2 comprises a physically distributed internet.

1 32. The communications system of claim 29, wherein the circuitry that routes
2 the call routes the call through a path including the PSTN assigns routing numbers to each
3 interface device from among a pool of reserved PSTN numbers and releases the routing
4 numbers upon call completion.

1 33. A communications system comprising:
2 a set of interface devices adapted to be coupled to a PSTN, the interface devices
3 configured to serve various geographic regions;
4 radio transceivers coupled to interface devices in the set of interface devices, the
5 radio transceivers for communication with mobile subscribers, the mobile subscribers each
6 having a home region; and
7 circuitry coupled to the set of interfaces that, for a call involving the PSTN and a
8 mobile subscriber located outside the mobile subscriber's home region, routes the call
9 through a path including an interface device that serves in the mobile subscriber's home
10 region;

11 wherein the path between the subscriber and the interface device in the mobile
12 subscriber's home region includes a portion of the PSTN.

1 34. The communications system of claim 33, wherein the portion of the path
2 through the PSTN between the subscriber and the interface device and the mobile
3 subscriber's home region is obtained based on a routing number assigned to the interface
4 that serves the region in which the subscriber is currently located.

1 35. The communications system of claim 33, wherein a control bus is included
2 in the circuitry that routes the call through a path including the interface device that serves
3 the mobile subscriber's home region, and wherein the control bus is coupled to (a) an
4 interface device to the PSTN that serves the subscriber's home region and (b) an interface
5 device to the PSTN that serves a region in which the subscriber is located.

1 36. A communications system comprising:
2 a set of interface devices adapted to be coupled to a PSTN, the interface devices
3 configured to service various geographic regions;
4 coupled to each interface device, a set of devices for communicating with radio
5 transceivers, each device for communicating with radio transceivers coupled to one or
6 more radio transceivers;
7 circuitry coupled to the set of interface devices that, with respect to calls from the
8 PSTN to mobile subscribers, has the same type of interface as the set of devices for
9 communicating with the radio transceivers, and wherein, if a call from the PSTN through
10 an interface device is directed to a subscriber in an area not serviced by the set of devices
11 for communicating with the radio transceivers coupled to the interface, routes the call to

an interface device coupled to a set of devices for communicating that service an area in which the subscriber is located.

37. The communications system of claim 36, the circuitry coupled to the set of interface devices routing the call without interrogating a centralized database.

38. The communications system of claim 36, the circuitry coupled to the set of interface devices routing the call without interrogating a home location register (HLR) and without interrogating a visited location register (VLR).

39. The communications system of claim 36, wherein the set of devices for communicating with the radio transceivers comprise radio port controllers (RPCs).

40. A communications system comprising:
a set of interface devices adapted to be coupled to a PSTN, the interface devices configured to service various geographic regions;
coupled to each interface device, a set of devices for communicating with radio transceivers, each device for communicating with radio transceivers coupled to one or more radio transceivers; and
circuitry coupled to the set of interface devices that, with respect to calls from subscribers to the PSTN, has the same type of interface as a port on the PSTN, and wherein, if a call from a subscriber located outside the subscriber's home area is direct to the PSTN, the circuitry coupled to the set of interface devices routes the call to an interface device that serves the subscriber's home area.

1 41. The communications system of claim 40, the circuitry coupled to the set of
2 interface devices routing the call without interrogating a centralized database.

1 42. The communications system of claim 40, the circuitry coupled to the set of
2 interface devices routing the call without interrogating a home location register (HLR) and
3 without interrogating a visited location register (VLR).

1 43. The communications system of claim 40, wherein the port on the PSTN
2 comprises a port of a class 5 switch.

1 44. A method of modifying an existing telephone network, the method
2 comprising:

3 locating interface devices in various geographic regions of the telephone network;
4 coupling the interface devices to the telephone network in the various geographic
5 regions, the interface devices coupled to circuitry coupled to radio transceivers that service
6 mobile subscribers that may be located in ones of the various geographic regions, the
7 mobile subscribers each being assigned to a respective geographic region;

8 wherein the interface devices are coupled to circuitry that, when a subscriber is
9 located in a region other than a geographic region to which the subscriber is assigned,
10 routes a call with the mobile subscriber through a path including a radio transceiver in the
11 region in which the mobile subscriber is currently located and an interface device in the
12 region to which the subscriber is assigned.

1 45. The method of claim 44, wherein the path between the radio transceiver
2 and the interface device in the region to which the subscriber is assigned includes an E1
3 link.

1 46. The method of claim 44, wherein, for calls with the subscriber located in a
2 region other than the geographic region to which the subscriber is assigned, billing
3 information is passed to the existing network regarding location of the subscriber only
4 through the interface in the region to which the subscriber is assigned.

1 47. A communications system comprising:
2 a set of interface devices adapted to be coupled to a PSTN, the interface devices
3 configured to be located in various geographic regions;
4 radio transceivers coupled to interface devices in the set of interface devices, the
5 radio transceivers for communication with mobile subscribers, the mobile subscribers each
6 having a home region; and
7 circuitry coupled to the set of interfaces that, for a call involving the PSTN and a
8 mobile subscriber located outside the mobile subscriber's home region, routes the call
9 through a path including an interface device in the mobile subscriber's home region;
10 wherein the path between the subscriber and the interface device in the mobile
11 subscriber's home region includes a portion of the PSTN.

ABSTRACT

Communications system comprising a set of interface devices adapted to be coupled to a public switch telephone network (PSTN) and radio transceivers. The interface devices are configured to serve in various geographic regions. The radio transceivers are coupled to the interface devices in the set of interface devices. The radio transceivers are for communication with mobile subscribers. The mobile subscribers each have a home region. The circuitry coupled to the set of interfaces routes a call through a path including an interface device that serves the mobile subscriber's home region, for a call involving the PSTN and a mobile subscriber located outside the mobile subscriber's home region.




FIG. 1




FIG. 2




FIG. 3

location registration




FIG. 4

originating call




FIG. 5

[illegible]

FIG. 6

inter-NIU handover




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR UTILITY PATENT APPLICATION**

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**METHOD AND APPARATUS FOR ROAMING IN HIERARCHIAL
MOBILE COMMUNICATIONS NETWORK**

the specification of which

 x is attached hereto.

 was filed on as Application Serial No.
and was amended on .
(If Applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a) which states in relevant part: "Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section....The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§ 1.97(b)-(d) and 1.98."

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate as indicated below and have also identified below any foreign application for patent or inventor's certificate on this invention having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)		Priority Claimed	
<u> </u>	<u> </u>	<u> </u>	<u> </u>
(Number)	(Country)	(Day/Month/Year Filed)	Yes No

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application

is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulation, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Patented, Pending, Abandoned)
-----------------------------------	------------------------	---

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Patented, Pending, Abandoned)
-----------------------------------	------------------------	---

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith, and to file, prosecute and to transact all business in connection with international applications directed to said invention:

Paul Davis	29,294
John J. Bruckner	35,816
Michael J. Murphy	37,404
David J. Weitz	38,362
Kent R. Richardson	39,443
David J. Abraham	39,554
U.P. Peter Eng	39,666
Henry J. Groth	39,696
George A. Willman	41,378
Jinntung Su	42,174
Travis L. Dodd	42,491
Barbara B. Courtney	42,442
Richard L. Gregory, Jr.	42,607
Van Mahamedi	42,828
Shantanu Basu	43,318

Address all correspondence to:

**George A. Willman
Wilson, Sonsini, Goodrich & Rosati
650 Page Mill Road
Palo Alto, CA 94304**

Direct all telephone calls to George A. Willman at (415) 493-9300.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Title 18, United States Code, §1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of
first inventor: Paul Berkowitz

Inventor's signature: _____

Date: _____

Citizenship: U.S.

Residence: Little Silver, New Jersey

Post Office Address: Same as above.

Full name of second joint
inventor, if any: Chauncey Shey

Inventor's signature: _____

Date: _____

Citizenship: U.S.

Residence: East Brunswick, New Jersey

Post Office Address: Same as above.

Full name of third joint
inventor, if any: Jan Vancraeynest

Inventor's signature: _____

Date: _____

Citizenship: Belgium

Residence: White Plains, New York

Post Office Address: Same as above

Full name of fourth joint
inventor, if any: Jose Vasconcellos

Inventor's signature: _____

Date: _____

Citizenship: U.S.

Residence: Morganville, New Jersey

Post Office Address: Same as above